

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 June 2004 (03.06.2004)

PCT

(10) International Publication Number
WO 2004/046698 A1

(51) International Patent Classification⁷: **G01N 21/64**,
H01L 27/14, H01J 43/04, H04N 5/32

(74) Agents: MURAKAMI, Tomokazu et al.; 4th Floor, Tsub-
aki Bldg., 10-2, Nishiikebukuro 5-chome, Toshima-ku,
Tokyo 171-0021 (JP).

(21) International Application Number:
PCT/JP2002/012022

(22) International Filing Date:
18 November 2002 (18.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): MIT-
SUI ENGINEERING & SHIPBUILDING CO., LTD.
[JP/JP]; 6-4, Tsukiji 5-chome, Chuo-ku, Tokyo 104-8439
(JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KIMURA, Noriaki
[JP/JP]; c/o Mitsui Engineering & Shipbuilding Co.,
Ltd. Tamano Works, 1-1, Tama 3-chome, Tamano-shi,
Okayama 706-8651 (JP). YUMII, Takayoshi [JP/JP]; c/o
Mitsui Engineering & Shipbuilding Co., Ltd. Tamano
Works, 1-1, Tama 3-chome, Tamano-shi, Okayama
706-8651 (JP).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: TWO-DIMENSIONAL WEAK RADIATION DETECTOR



(57) **Abstract:** A weak light detector (40) which can detect two-dimensional weak radiation at a high speed with high precision. The fluorescence from the DNA chip (46) is incident on a detection part (56) of a detection unit (52). The detection unit (56) has a detection module with a number of detection transistors being placed to correspond to cells of the DNA chip (46). The detection part (56) performs photoelectric conversion of the incident fluorescence (photon) to emit electrons, and amplifies the electrons to make them incident on the detection module. The detection transistors are switched based the Hadamard matrix to operate. A data processing unit (54) reads an output signal of the detection part (56), then performs Hadamard inversion, and determines the detection transistor which outputs the signal.